

**2025 Series
Horizontal
Spin Trimmer**



From Blow Molder to Box MTM Systems is Your Answer For Auxiliary Equipment

Features	Benefits
Heated blade technology	Trim virtually any type of resin, including PETG, barrier resins, K resins, PVC, PP, PE; multi layer resins respond especially well.
New redesigned blade holder	Allows the blade to nest at the correct angle without a lengthy setup period. Reduced blade changeover time.
New redesigned blade holder adjustment	Designed to keep left hand and right hand blades in perfect alignment from the log centerline. Reduces changeover times and provides greater consistency.
Heavy duty 1/3 hp with DC variable speed controller	Long life and greater consistency in throughput. Allows various line speeds to be run on a single trimmer.
New two pulley drive system with "V" Guide timing belt	Allows for better control of containers during the trimming process with no slippage on the drive pulleys.
Simplified belt tensioning	Allows for quick changeovers increasing productivity. Reduces chance for operator error during procedure.
PLC controls with panel mounted user interface	Reduces setup time and functions as a fault message panel.
Adjustable bottle discharge chutes with removable sides	Allows for quick changeovers increasing productivity.
Jam and incorrect trim detection	Reduces down time and eliminates incorrectly trimmed containers.
Stainless steel infeed chute with bottle metering	Proper bottle spacing and positive feed.
Audible alarm and beacon lights for detection devices	Faster response time from plant staff. Higher production.

Specifications

Dimensions:		Utility Requirement:	
Width	40"	Electrical Supply	
Length	72"	Voltage	120VAC
Height	89"	Amperage	15 Amp
Weight	700 lbs.		
Vertical Height		Compressed Air Supply	
Range	44" ± 3" Height from floor to blade	Line Size	1/4" Pipe
		Pressure	80-100 psi
Motor Ratings:		Container Range:	
Trimmer Drive Motor	1/3 hp	Logs per minute	300 (depending on size)
		Min/Max neck size	1.5" – 7" 25 – 127 mm
		Min/Max diameter	1" – 4" 38 – 178 mm
Heater Blade Temperature	450°F (Max)	Min/Max height	3" – 18" 76 – 450 mm

Specifications are subject to change without notice. Guards are supplied and must be in place before operation. All sales are subject to our prevailing terms and conditions of sale. Other options available upon request.

Lectro Engineering Company
1643 Lotsie
St. Louis, MO 63132 USA

Phone 314-567-3100
Fax 314-567-3466
www.lectrotreat.com

DVD & CD available to show application & operation